

cluster.conf 1

cluster.conf

- Basic configuration : RHCS (3) Node + Fence
- Basic Two-Node configuration : Node + Fence
- Add-ons configuration : Node + Fence + resource

Basic configuration

cluster.conf|

```
<cluster name="mycluster" config_version=1">
  <clusternodes>
    <clusternode name="node01" nodeid=1">
      <fence>
      </fence>
    </clusternode>
    <clusternode name="node02" nodeid=2">
      <fence>
      </fence>
    </clusternode>
    <clusternode name="node03" nodeid=3">
      <fence>
      </fence>
    </clusternode>
  </clusternodes>
  <fencedevices>
  </fencedevices>
  <rm>
  </rm>
</cluster>
```

Basic Two-Nodes Configuration cluster.conf|

```
<cluster name="mycluster" config_version="2">
  <cman two_node="1" expected_votes="1"/>
  <clusternodes>
    <clusternode name="node01" nodeid="1">
      <fence>
      </fence>
    </clusternode>
    <clusternode name="node02" nodeid="2">
      <fence>
      </fence>
    </clusternode>
  </clusternodes>
  <fencedevices>
  </fencedevices>
  <rm>
```

```
</rm>  
</cluster>
```

From:

<http://allthatlinux.com/dokuwiki/> - **AllThatLinux!**

Permanent link:

http://allthatlinux.com/dokuwiki/doku.php?id=cluster.conf_%EA%B5%AC%EC%A1%B0

Last update: **2019/01/23 18:30**

