

목차

파일 백업 스크립트	3
------------------	---

파일 백업 스크립트

예제

```
#####
# rhvm Backup script #
# create : KangWoo Lee #
# date : 2013.03.12 #
# #
# Variables #
# DEST_DIR : backup archive creating directory #
# TARGETS : backup target files #
# #
#####
#!/bin/sh
DEST_DIR=.
DATE=`date +%F`
LINE="===== "

echo $LINE
echo "[${DATE}] Backup Script Start"
echo $LINE

# Backup Target define

TARGETS=(
/etc/jbossas/jbossas.conf
/etc/rhvm/
/etc/yum/pluginconf.d/versionlock.list
/etc/pki/rhvm/
/etc/jbossas/rhvm-slimmed/
/var/lib/jbossas/server/rhvm-slimmed
/usr/share/rhvm-reports-server/buildomatic
/usr/share/rhvm/conf/iptables.example
/usr/share/rhvm/kerberos/krb5.conf
/usr/share/rhvm/dbscripts/create_db.sh.log
/usr/share/rhvm/rhvm.ear/rhevmanager.war/ExternalConfig.txt
/usr/share/rhvm/rhvm.ear/rhevmanager.war/ServerParameters.js
#/usr/share/rhvm-reports/reports-
INSERT_VERSION_NUMBER/resources/organizations/rhvmreports/Resources/JDBC/data_sources/rhvm.xml
#/usr/share/rhvm-reports/reports-
INSERT_VERSION_NUMBER/users/rhvmreports/rhvm-002dadmin.xml
/usr/share/rhvm-reports/
#/usr/share/rhvm-reports-server/buildomatic/default_master.properties
#/usr/share/rhvm-reports-server/buildomatic/install.xml
#/usr/share/rhvm-reports-server/buildomatic/setup.xml
```

```
/usr/share/rhevms-reports-server/buildomatic/  
/root/.pgpass  
/root/.rnd  
)  
  
# Destination directory check  
if [ ! -e $DEST_DIR ]  
then  
    echo "Destination directory is NOT EXISTS! creating..."  
    mkdir -p $DEST_DIR  
fi  
  
# File Check  
for T in ${TARGETS[*]}  
do  
    #echo $T  
    if [ -e $T ]  
    then  
        echo "$T is exists"  
    else  
        echo "$T is not exists"  
    fi  
done  
  
# Backup Archive Create  
tar -cvzf $DEST_DIR/rhevms_backup-$DATE.tgz ${TARGETS[*]}  
  
echo $LINE  
echo "Backup End"  
echo $LINE
```

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://atl.kr/dokuwiki/doku.php/%ED%8C%8C%EC%9D%BC%EB%B0%B1%EC%97%85_%EC%8A%A4%ED%81%AC%EB%A6%BD%ED%8A%B8

Last update: 2017/02/08 08:50

