

목차

baremetal node get system uuid 3

참조링크 3

baremetal node get system uuid

```
$ openstack baremetal introspection data save  
9dcc87ae-4c6d-4ede-81a5-9b20d7dc4a14 | jq .extra.system.product.uuid  
"F5055C6C-477F-47FB-AFE5-95C6928C407F"
```

이 값을 이용하여 heat template의 노드별 설정값을 별도로 지정할 수 있다.

```
resource_registry:  
  OS::Triple0::ComputeExtraConfigPre: /usr/share/openstack-tripleo-heat-  
  templates/puppet/extraconfig/pre_deploy/per_node.yaml  
parameter_defaults:  
  NodeDataLookup: '{"F5055C6C-477F-47FB-AFE5-95C6928C407F":  
{ "nova::compute::vcpu_pin_set": [ "2", "3" ] } }'
```

또는 각 노드의 NIC 설정을 지정할 수 있다.

```
resource_registry:  
  OS::Triple0::NodeUserData: /usr/share/openstack-tripleo-heat-  
  templates/firstboot/os-net-config-mappings.yaml  
parameter_defaults:  
  NetConfigDataLookup:  
    control0:  
      dmiString: 'system-uuid'  
      id: 'd1259a88-6d31-11ec-860f-3a68dd6cbf33'  
      nic1: "enp1s0"  
      nic2: "enp2s0"  
      nic3: "enp3s0"  
      nic4: "enp9s0"  
      nic5: "enp10s0"
```

참조링크

- https://access.redhat.com/documentation/en-us/red_hat_opensstack_platform/13/html/advanced_overcloud_customization/chap-configuration_hooks

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://atl.kr/dokuwiki/doku.php/baremetal_node_get_system_uuid

Last update: 2022/08/30 05:14



