

목차

Context.xml 3

— 이강우 2015/08/03 16:13

Context.xml

```
<?xml version='1.0' encoding='utf-8'?>

<Context docBase="/software/docroot/app.war" privileged="true"
reloadable="true">
<!-- ### MySQL JDBC JNDI - 1node ###
    <Resource name="jdbc/mysql" auth="Container"
        type="javax.sql.DataSource"
        maxActive="100"
        maxIdle="30"
        maxWait="10000"
        username="USERNAME"
        password="PASSWORD"
        driverClassName="com.mysql.jdbc.Driver"
        removeAbandonedOnBorrow="true"
    removeAbandonedTimeout="60"
        logAbandoned="true"
        validationQuery="select 1"
        url="jdbc:mysql://IPADDRESS:PORT/DBNAME?autoReconnect=true"
    />
-->
<!-- ### Oracle JDBC JNDI - 1node ###
    <Resource name="jdbc/JNDINAME" auth="Container"
        type="javax.sql.DataSource"
        maxActive="100"
        maxIdle="30"
        maxWait="10000"
        username="USERNAME"
        password="PASSWORD"
        driverClassName="oracle.jdbc.driver.OracleDriver"
        removeAbandonedOnBorrow="true"
        removeAbandonedTimeout="60"
        logAbandoned="true"
        validationQuery="select 1 from dual"
        url="jdbc:oracle:thin:@localhost:1521:SID" />
-->
<!-- ### Oracle RAC JDBC JNDI - 2node ###
    <Resource name="jdbc/jndiname" auth="Container"
        type="javax.sql.DataSource"
        maxActive="100"
        maxIdle="30"
        maxWait="10000"
        username="USERNAME"
        password="PASSWORD"
        driverClassName="oracle.jdbc.driver.OracleDriver"
```

```
        removeAbandonedOnBorrow="true"
        removeAbandonedTimeout="60"
        logAbandoned="true"
        validationQuery="select 1 from dual"
url="jdbc:oracle:thin:@(description=(address_list=(load_balance=on)(failover=on)(address=(protocol=tcp)(host=1.1.1.1)(port=1521))(address=(protocol=tcp)(host=2.2.2.2)(port=1521)))(connect_data=(service_name=SERVICE_NAME)(failover_mode=(type=select)(method=basic))))" />
-->
<!-- ### Oracle RAC JDBC JNDI - 4node ###
    <Resource name="jdbc/JNDI_NAME" auth="Container"
        type="javax.sql.DataSource"
        maxActive="100"
        maxIdle="30"
        maxWait="10000"
        username="USERNAME"
        password="PASSWORD"
        driverClassName="oracle.jdbc.driver.OracleDriver"
        removeAbandonedOnBorrow="true"
        removeAbandonedTimeout="60"
        logAbandoned="true"
        validationQuery="select 1 from dual"
url="jdbc:oracle:thin:@(description=(address_list=(load_balance=on)(failover=on)(address=(protocol=tcp)(host=1.1.1.1)(port=1521))(address=(protocol=tcp)(host=2.2.2.2)(port=1521))(address=(protocol=tcp)(host=3.3.3.3)(port=1521))(address=(protocol=tcp)(host=4.4.4.4)(port=1521)))(connect_data=(service_name=SERVICE_NAME)(failover_mode=(type=select)(method=basic))))" />
-->
</Context>
```

From:

<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:

https://atl.kr/dokuwiki/doku.php/conf_engine_host_root.xml?rev=1776763692

Last update: **2026/04/21 09:28**

