

목차

deployment failed 상태 해결방법	3
참조링크	4

deployment failed 상태 해결방법

overcloud stack을 삭제해도 provision state가 꼬였는지 failed로 나오는 경우가 있다

```
[stack@manager templates]$ openstack baremetal node list
```

UUID	Name	Instance UUID	Power State	Provisioning State	Maintenance
f3096509-1e5b-46e3-8c69-9d6018c30af8	controller1	d38378e5-de86-42ca-9377-5b8884f6fc3e	power off	deploy failed	False
1719a73c-d60c-460d-a3d4-b33a72daa428	compute1	ae3ecb82-54d7-4a14-b8e3-256a591039c4	power off	deploy failed	False

이럴때는 해당 instance uuid를 unset 하고 해당 상태를 다시 undeploy 상태로 변경한다

```
openstack baremetal node unset --instance-uuid
f3096509-1e5b-46e3-8c69-9d6018c30af8
openstack baremetal node unset --instance-uuid 1719a73c-d60c-460d-a3d4-
b33a72daa428

openstack baremetal node undeploy 1719a73c-d60c-460d-a3d4-b33a72daa428
openstack baremetal node undeploy f3096509-1e5b-46e3-8c69-9d6018c30af8
openstack baremetal node list
```

UUID	Name	Instance UUID	Power State	Provisioning State	Maintenance
f3096509-1e5b-46e3-8c69-9d6018c30af8	controller1	None	power off	available	False
1719a73c-d60c-460d-a3d4-b33a72daa428	compute1	None	power off	available	False

참조링크

- <https://www.kangtaeho.com/24>

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://atl.kr/dokuwiki/doku.php/deployment_failed_%EC%83%81%ED%83%9C_%ED%95%B4%EA%B2%B0%EB%B0%A9%EB%B2%95

Last update: 2022/11/25 07:29

