목차

RabbitMQ Installation 3
CentOS 7 repository 설정 3
설치 3
정지/기동 3

RabbitMQ Installation

CentOS 7 repository 설정

```
[bintray-rabbitmq-server]
name=bintray-rabbitmq-rpm
baseurl=https://dl.bintray.com/rabbitmq/rpm/rabbitmq-server/v3.8.x/el/7/
gpgcheck=0
repo_gpgcheck=0
enabled=1

[rabbitmq_erlang]
name=rabbitmq_erlang
baseurl=https://packagecloud.io/rabbitmq/erlang/el/7/$basearch
repo_gpgcheck=1
gpgcheck=1
enabled=1
# PackageCloud's repository key and RabbitMQ package signing key
gpgkey=https://packagecloud.io/rabbitmq/erlang/gpgkey
       https://dl.bintray.com/rabbitmq/Keys/rabbitmq-release-signing-key.asc
sslverify=1
sslcacert=/etc/pki/tls/certs/ca-bundle.crt
metadata_expire=300
```

설치

```
yum -y install rabbitmq-server
```

정지/기동

설치 이후 `rabbitmq-server` 를 구동하려면 아래 명령어를 사용하도록 한다.

```
systemctl start rabbitmq-server
```

`rabbitmq-server`의 *openfiles(nofile)* 를 수정하려면 아래 파일의 옵션을 수정하도록 한다.

```
# To override LimitNOFILE, create the following file:
#
# /etc/systemd/system/rabbitmq-server.service.d/limits.conf
#
# with the following content:
```

```
#
# [Service]
# LimitNOFILE=65536

LimitNOFILE=32768
```

From:
https://atl.kr/dokuwiki/ - **AllThatLinux!**

Permanent link:
https://atl.kr/dokuwiki/doku.php/rabbitmq_installation

Last update: **2020/04/14 05:20**