

목차

RedHat - Undercloud 삭제 3

overcloud 삭제 3

Undercloud 삭제 3

 참조링크 4

RedHat - Undercloud 삭제

overcloud 삭제

일단 [RedHat - Overcloud 삭제](#)를 먼저 보고 overcloud를 삭제하여야 한다.

- OSP 13, 10 버전

```
heat stack-list
heat stack-delete <UUID>
openstack overcloud plan delete overcloud
```

- OSP 16버전

```
openstack overcloud delete <overcloud stack name>
```

- overcloud ironic node 삭제

```
openstack baremetal node delete $(openstack baremetal node list -f value -c
UUID)
```

Undercloud 삭제

아래 프로세스에 따라 언더클라우드를 삭제하고 재설치를 진행할 수 있다.

```
source stackrc
if [[ $(grep -oP "[0-9]+" /etc/rhosp-release) -ge 16 ]]; then
    echo "OSP16+ deleting overcloud and containers";
    openstack overcloud delete overcloud -y
    sudo podman rm -f $(sudo podman ps -aq)
    sudo podman rmi $(sudo podman images -q)
fi
rm /home/stack/undercloud-passwords.conf
systemctl list-unit-files | grep openstack | awk '{print $1}' | xargs -I {}
sudo systemctl stop {}
systemctl list-unit-files | grep neutron | awk '{print $1}' | xargs -I {}
sudo systemctl stop {}
sudo systemctl stop docker
sudo systemctl stop podman
sudo systemctl stop keepalived
sudo rm -rf /var/lib/mysql /var/lib/rabbitmq /etc/keystone
/opt/stack/.undercloud-setup /root/stackrc /home/stack/stackrc
```

```

/var/opt/undercloud-stack /var/lib/ironic-discoverd/discoverd.sqlite
/var/lib/ironic-inspector/inspector.sqlite /home/stack/.instack
/root/tripleo-undercloud-passwords /var/lib/registry /etc/pki/ca-
trust/source/anchors/cm-local-ca.pem /httpboot/ /tftpboot/ /srv/*
/var/lib/docker /etc/os-net-config/config.json
dirs="ceilometer heat glance horizon ironic ironic-discoverd keystone
neutron nova swift haproxy"; for dir in $dirs; do sudo rm -rf /etc/$dir ;
sudo rm -rf /var/log/$dir ; sudo rm -rf /var/lib/$dir; done
sudo yum remove -y rabbitmq-server mariadb haproxy openvswitch keepalived
$(rpm -qa | grep openstack) python-tripleoclient docker os-collect-config
os-net-config
sudo rm -rf /etc/httpd/conf.d/10*
sudo rm -rf /etc/httpd/conf.d/25*
sudo rm -rf /etc/httpd/conf.d/openstack-tripleo-ui.conf.rpmsave
sudo sed -i '/:3000/d ; /:35357/d ; /:5000/d ; /:8042/d ; /:8774/d ;
/:8777/d' /etc/httpd/conf/ports.conf
sudo rm -rf /etc/pki/tls/certs/undercloud*
sudo rm -rf /etc/pki/tls/private/undercloud*
sudo rm -rf /etc/pki/ca-trust/source/anchors/*local*
sudo rm -rf /etc/sysconfig/network-scripts/ifcfg-br-ctlplane
sudo mv /etc/os-net-config/config.json /etc/os-net-config/config.json.orig
sudo sed -i '/ovs/d ; /OVS/d' /etc/sysconfig/network-scripts/ifcfg-eth1
#####
#####
#####
#!!!! remove all interface configuration which is related to openvswitch
from /etc/sysconfig/network-scripts, e.g. ifcfg-br_int, ifcfg-ovs_system,
ifcfg-brctlplane, etc. roll back the configuration of the local
interface!!!!
#####
#####
#####
#!!!! Starting from RHOSP 12 /root/.my.cnf file should also be removed:
sudo rm /root/.my.cnf
#####
#####
#####
#
# With containerized undercloud, we also need to delete /var/lib/config-
data/
sudo rm -rf /var/lib/config-data
sudo rm -rf /etc/cloud/
sudo reboot

```

참조링크

- <https://access.redhat.com/solutions/2210421>

From:

<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:

https://atl.kr/dokuwiki/doku.php/redhat_-_undercloud_%EC%82%AD%EC%A0%9C

Last update: **2021/07/27 06:46**

