

목차


```
#version=RHEL7
# System authorization information
auth --enableshadow --passalgo=sha512

# Use CDROM installation media
cdrom
# Run the Setup Agent on first boot
firstboot --enable
ignoredisk --only-use=sda
# Keyboard layouts
keyboard --vckeymap=us --xlayouts='us'
# System language
lang en_US.UTF-8

# Network information
network --bootproto=dhcp --device=enol6777736 --ipv6=auto --activate
network --hostname=rhcs3
# Root password
rootpw --iscrypted
$6$xrBseKMavU4Z0EBi$pQ4uZ/hV97jhfrJQWLnt0PvzDzSSUEh0HPo/BQ1h7e9wFw1VbpMLAvMU
yvHtRfPcwcPHCcCcFZK0BaT6F1bu00
# System services
services --enabled="chronyd"
# System timezone
timezone Asia/Seoul --isUtc
# System bootloader configuration
bootloader --location=mbr --boot-drive=sda
autopart --type=lvm
# Partition clearing information
clearpart --none --initlabel

%packages
@core
chrony

%end
```

From:
<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:
https://atl.kr/dokuwiki/doku.php/rhel7_kickstart

Last update: **2015/06/18 15:49**

