

목차

STONITH 비활성화 3

참조링크 3

STONITH 비활성화

일반적으로 내부 테스트나 간단한 클러스터 구성시에 굳이 Fence가 필요없는 경우가 있다. Pacemaker는 기본적으로 STONITH가 구성되어있지 않으면 리소스 그룹이 수행되지 않는다.

```
Dec 4 18:18:30 rhcs1 crmd[7548]: notice: State transition S_IDLE ->
S_POLICY_ENGINE
Dec 4 18:18:30 rhcs1 pengine[7547]: error: Resource start-up disabled
since no STONITH resources have been defined
Dec 4 18:18:30 rhcs1 pengine[7547]: error: Either configure some or
disable STONITH with the stonith-enabled option <-- 이부분
Dec 4 18:18:30 rhcs1 pengine[7547]: error: NOTE: Clusters with shared
data need STONITH to ensure data integrity
Dec 4 18:18:30 rhcs1 pengine[7547]: notice: Calculated transition 1,
saving inputs in /var/lib/pacemaker/pengine/pe-input-1.bz2
Dec 4 18:18:30 rhcs1 pengine[7547]: notice: Configuration ERRORS found
during PE processing. Please run "crm_verify -L" to identify issues.
Dec 4 18:18:30 rhcs1 crmd[7548]: notice: Transition 1 (Complete=0,
Pending=0, Fired=0, Skipped=0, Incomplete=0,
Source=/var/lib/pacemaker/pengine/pe-input-1.bz2): Complete
Dec 4 18:18:30 rhcs1 crmd[7548]: notice: State transition
S_TRANSITION_ENGINE -> S_IDLE
```

이런경우 STONITH를 비활성화 하여 문제를 해결할 수 있다.

```
# pcs property set stonith-enabled=false
# crm_verify -L

# 다시 활성화
# pcs property set stonith-enabled=true
```

참조링크

- http://clusterlabs.org/pacemaker/doc/en-US/Pacemaker/1.1/html/Clusters_from_Scratch/ch05.html
- <https://access.redhat.com/solutions/2476841>

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://atl.kr/dokuwiki/doku.php/stonith_%EB%B9%84%ED%99%9C%EC%84%B1%ED%99%94

Last update: 2022/09/15 08:32

